

## 鑄型壓克力圓管規格

Standard Length : 1200mm / 1000mm

外徑 (mm)	厚度 (mm)						
	2	3	4	5	6	8	10
25	●	●					
30	●	●	●				
35	●	●	●				
40	●	●	●	●			
45	●	●	●	●			
50	●	●	●	●	●	●	●
60	●	●	●	●	●	●	●
65	●	●	●	●	●	●	●
70	●	●	●	●	●	●	●
80	●	●	●	●	●	●	●
90		●	●	●	●	●	●
100		●	●	●	●	●	●
110		●	●	●	●	●	●
120		●	●	●	●	●	●
125		●	●	●	●	●	●
130		●	●	●	●	●	●
140		●	●	●	●	●	●
150		●	●	●	●	●	●
152		●	●	●	●	●	●
160		●	●	●	●	●	●

鑄型壓克力圓管規格

外徑 (mm)	厚度(mm)						
	2	3	4	5	6	8	10
170		●	●	●	●	●	●
180		●	●	●	●	●	●
200		●	●	●	●	●	●
230			●	●	●	●	●
250			●	●	●	●	●
267			●	●	●	●	●
300			●	●	●	●	●
330				●	●	●	●
350			●	●	●	●	●
400			●	●	●	●	●
450			●	●	●	●	●
500				●	●	●	●
600				●	●	●	●

## 鑄型壓克力圓管特色

- 優良的耐候性。
- 透光性極佳，透光率可達92%，有著如水晶般晶瑩剔透的特性。
- 機械加工簡易且方便。

## 鑄型壓克力圓管應用

- 透明包裝容器
- 魚缸

## 鑄型壓克力圓管規格-客製化

- 不可與其他有機溶劑同存一處，更不能讓其接觸有機溶劑。
- 不能在溫度超過85°C的環境下使用。

星銘產品

[壓克力圓管](#) [壓克力圓棒](#) [壓克力板&厚板](#)

[壓克力配件](#) [壓克力導光條](#) [壓克力補強條&壓克力異型品](#)

[壓克力擴散板, 導光板, 反射片](#) [壓克力窗簾棒](#) [鑽石拋光機](#)